



Your Infection Control Specialist™



Taking control of your infection control



How automated washer-disinfectors in dental practices improve the sterilization process

The use of automated instrument washer-disinfectors (WD) is growing worldwide as regulatory authorities and dentists endorse and adopt what has come to be understood as the most effective and consistent means of cleaning and disinfecting instruments before sterilization.



The hazards of manual cleaning

Hand scrubbing is increasingly used less because it exposes staff to the hazards of skin punctures and can affect the productivity of the practice as it takes time away from patient care.

The limitations of ultrasonic cleaning

Ultrasonic cleaning is also used but its effectiveness compared to automated washing has long been under question. Ultrasonic cleaning requires subsequent rinsing before sterilization, adding steps to sterilization efficiency.

The challenge in both these methods is the effect on human resources. As Mark Tholen writes in Dental Economics, "Decontaminating, washing, rinsing, and drying instruments are extremely labor intensive and dramatically reduce the throughput speed of instrumentation through sterilization."*

He points to the automated washer as the single greatest labor-saving device in a dental office, concluding that, "when [a washer is] used in combination with cassettes, approximately one hour of labor can be saved for every nine procedural set-ups that are processed through sterilization."*

Delivering consistent, validated cleaning results

Consistent repeatable cycles are a key advantage to using automated washers because this offers the user control. It ensures every set of instruments receives the same validated cleaning process, and cycle data is recorded to provide accurately detailed and consistent documentation that establishes an accountability baseline for instrument cleaning.

* Tholen, Mark, 10 Ideas to Increase Production and Decrease Expenses in Sterilization. (www.dentaleconomics.com/articles/print/volume-99/issue-10/features/increase-productionand-decrease-expenses-in-sterilization.html)

HYDRIM meets the Internet

The HYDR/M G4 is equipped with a web interface that enables online access and offers a platform with endless possibilities.







A high-resolution, 65K color touch screen offers a vivid display of messages, current cycle information and customizable colors all with extraordinary clarity. Fully adjustable contrast levels let you optimize the screen to the lighting in your steri-center, and it's 2.5-inch by 3-inch dimensions allow easy viewing of cycle information.

CONNECT

The HYDR/M G4 is capable of communicating directly with service personnel or anyone you choose. Should the HYDR/M G4 ever need attention, diagnostic information can be sent via email to pre-selected dealer service reps, significantly reducing down time.



PROTECT



Patient safety relies on attention to detail. The HYDRIM G4 supports verifiable processes that are PIN protected with user-defined IDs so that staff members can be required to authorize a cycle. This encourages extra attention to process and creates a safer environment for both staff and patient.

COLLECT

With each cycle, information must be stored to protect your office and your patients. The integrated data logger stores all cycle information for the lifetime of the unit. A

USB port allows for the manual retrieval of cycle history. The 10/100 Base-T Ethernet connection puts your PC in direct contact with your HYDR/M G4 and the RS232 serial printer port allows you to connect with an external printer.





HYDRIM C61wd G4 washer-disinfector

BENEFITS

- Designed in accordance with ISO 15883-1 and -2, the international standard for washer-disinfectors
- The unit can be installed on the countertop or built into a steri-center under the counter
- Large chamber volume 6 full sized IMS cassette capacity, the HYDRIM C61wd G4 can turn over 120 instruments in just 60 minutes – start to dry
- G4 web portal interface includes data storage, service logs and remote access capabilities
- Validated cycles to ensure repeatable washing and disinfection performance
- HIP ULTRA cleaning solution is stored in the unit, so there are no extra storage space requirements
- Improved serviceability, reliability and minimal maintenance requirements
- Robust stainless steel exterior
- Vivid color touch screen
- Active drying with a HEPA filter
- Optional Lumen Cleaning System (LCS) for C61wd-LCS G4 cleans up to 8 handpieces
- The LCS has a reusable water filter

SPECIFICATIONS

Size:

Dimensions: (w x h x d) 598 x 520 x 526 mm

Depth with door open: 829 mm

Weight: 44 kg

Cycle Times'

Rinse and Hold 5 mins

Regular Wash + Dry 26 mins. + 10 mins.

Heavy Duty Wash with Disinfection + Dry 42 mins. + 10 mins.

Water Consumption Per Cycle[†]

Rinse and Hold 11 litres
Regular Wash 11 litres
Heavy Duty Wash & Disinfection 30 litres

Electrical Connection[‡]

Electrical Rating: 208-240V or 200-230V, 50 Hz or 60 Hz, 12A, single phase


Water and Drain Connections

Hot and Cold Water Tap Connection
Recommended Hot Water Temperature
Cold Water Temperature
Cold Water Temperature
Cold Water Pressure
Drain

3/4" Garden hose, male
60°C
<30°C
1 - 10 bar
2 cm

- * Actual cycle times will vary with incoming water temperature and pressure.
- [†] Water consumption includes drying
- [‡] Electrical requirements are model specific

ACCESSORIES



Basket rack p/n 01-113257 16" x 6" x 1.5" (407 x 153 x 38 mm)



Six cassette rack p/n 01-113251 17" x 15" x 5" (424 x 390 x 120 mm)



Four double stacked cassette p/n 01-113252 16" x 15" x 5" (407 x 380 x 127 mm)



Three cassette, two basket rack p/n 01-113253 16" x 15" x 5" (407 x 380 x 127 mm)













HYDRIM C61wd G4 HYDRIM C61wd-LCS G4



Lumen Cleaning System (Compatible with LCS model only) p/n 01-113625



Large basket p/n 01-113545 16" x 15" x 2" (424 x 390 x 56 mm)



Basket with hinged lid p/n 01-113547 8.5" x 7" x 2" (216 x 172 x 54 mm)



HIP ULTRA cleaning solution p/n CS-HIPC-U (8 X 750 ml)



BENEFITS

- Designed in accordance with ISO 15883-1 and -2, the international standard for washer-disinfectors
- HYDR/M M2 G4 can process 1,500 instruments in a 10-hour day
- Under counter steri-center installation, but can also be a freestanding unit
- G4 web portal interface includes data storage, service logs and remote access capabilities
- Validated cycles to ensure repeatable washing and disinfection performance
- Ten 8" x 11" IMS cassette capacity
- HIP cleaning solution is stored in the unit, so there are no extra storage space requirements
- USB port for data storage
- Robust stainless steel exterior
- Vivid color touch screen
- Active drying with a HEPA filter
- Optional Lumen Cleaning System (LCS) cleans up to 12 handpieces
- The LCS has a reusable water filter

SPECIFICATIONS

| Size: | |
|-------------------------|--------------------|
| Dimensions: (w x h x d) | 600 x 850 x 600 mm |
| Depth with door open: | 1200 mm |
| Weight: | 90 kg |
| Cycle Times* | |
| Rinse and Hold | 18 mins |

| Rinse and Hold | 18 mins |
|---|---------------------|
| Regular Wash + Dry | 35 mins. + 30 mins. |
| Heavy Duty Wash with Disinfection + Dry | 60 mins. + 30 mins. |

| Water Consumption Per Cycle [†] | | | | |
|--|-----------|--|--|--|
| Rinse and Hold | 16 litres | | | |
| Regular Wash | 32 litres | | | |
| Heavy Duty Wash & Disinfection | 40 litres | | | |

| Electrical Connection | | | | | |
|-----------------------|---------------------------|--|--|--|--|
| Electrical Rating: | 230-240V, 50 Hz or 60 Hz, | | | | |
| | 12A or 13A, single phase | | | | |

| Water and Drain Connections | | | | | |
|-----------------------------|-----------------------------------|------------------------|--|--|--|
| | Hot and Cold Water Tap Connection | 3/4" Garden hose, male | | | |
| | Recommended Hot Water Temperature | 60°C | | | |
| | Cold Water Temperature | < 30°C | | | |
| | Inlet Water Pressure | 2-5 bar | | | |
| | Drain | 2 cm | | | |

 $^{^{\}star}$ Actual cycle times will vary with incoming water temperature and pressure.

ACCESSORIES



Hinged instrument rack p/n 01-110409S 7.5" x 4" x 4.3" (192 x 100 x 109 mm)



Basket with hinged lid, 1/4 size p/n 01-109966S 6" x 8.5" x 2" (159 x 216 x 51 mm)



Lumen Cleaning System p/n 01-113776S




STAT/M 2000 Basket p/n 01-107240 11" x 7" x 1.5" (275 x 178 x 38 mm)

[†] Water consumption includes drying

[‡] Electrical requirements are model specific



HYDRIM M2 G4



STAT/M 5000 Basket P/N/ 01-107241 14" x 7" x 1.25" (373 x 178 x 32 mm)



Long Basket p/n 01-108232 18" x 6" x 1.5" (442 x 150 x 38 mm)



Cleaning Solution Bottle CS-HIPL Case of 2 x 3.8 L



5-Cassette Rack, Full Size p/n 01-109963S 19" x 13" x 6" (480 x 335 x 158 mm)



5-Cassette Rack, Half Size p/n 01-109964S 19" x 7" x 6" (480 x 168 x 158 mm) Cassette autoclave



STATIM® 5000 G4

Cassette autoclave



BRAVO

Vacuum chamber autoclave



OPTIM® 33TB

Surface cleaner and disinfectant



STAT*MATIC*™

Automatic handpiece maintenance unit



STATMATIC[™]PLUS

Automatic handpiece maintenance and cleaning unit



SANAO™†

Handpieces




STAT/S®†

Hign speed handpieces



STATMAT

Silicone mat for STATIM autoclaves



Manufactured by:

SciCan Ltd.

1440 Don Mills Rd., Toronto, Ontario M3B 3P9 Phone (416) 445-1600 • Fax (416) 445-2727 Toll Free 1-800-667-7733

custservice.ca@scican.com

 ϵ

*Manufactured by:

SciCan GmbH **EU Representative**

Wangener Strasse 78 88299 Leutkirch GERMANY Tel.: +49 (0)7561 98343 - 0 Fax: +49 (0)7561 98343 - 699

CE

FOLLOW US ON:



Facebook: SciCan



Twitter: @SciCan

Consult your local sales representative for product availability.

